

The SL Balefeeder Range

Our SL range of feeders provide an economical option for farmers who primarily feed out round bales.

SL feeders are simple, reliable machines that tackle many of the problems commonly found on chain feeders.

Although designed for round bales, SL feeders are able to handle square bales when fitted with the optional side bars.

The SL-350 and SL-700 use the same feed unit, matched to different bale loading systems, and share these advantages:

1: SIMPLE, RUGGED DESIGN

From the 12,000lb chain to the heavy-duty bearings, the SL feeders are built to work hard and keep working.

2: SAFE AND EASY

We designed the SL feeders to be super easy and safe machines to use with the single hydraulic function and high bale support.

3: FULLY ENCLOSED FLOOR

We specify a polyethylene floor because it is slippery, non-corroding and extremely durable.



Single bale feeder
Massive 12,000lb zinc-plated roller chains
Replaceable zinc-plated RHS chain bars
Direct-drive system
Enclosed rollers
High hook position for superior rigidity
CAT 1 and CAT 2 top & lower links
High back frame holds bale in place

The SL-350 Balefeeder

The SL-350 is a 3 point linkage mounted single balefeeder suitable for all types of round bales, even 5' long. The unit weighs just 460 kilograms and will feed out both sides.

SELF-LOADING

Loading the SL-350 is very simple using our proven self-loading system. First the feeding cradle is disconnected by the pull of a rope. The tractor backs up and picks up the bale and moves it to the platform.

The operator can then stop to remove the net wrap before placing the bale on the platform. Its very low cradle with no crossbar makes bale loading easy and quick.

The operator then drives the forks into the feed unit, easy to line up correctly because of its unequal length tynes, and is now ready to feed out.

High-mounted hook latch	Outboard mounted double sealed heavy-duty 4-bolt bearings	Ultra low cradle for loading	Fully enclosed non-corroding floor to eliminate feed waste	Massive 12,000lb roller chain, shown compared to conventional chain	High back bar to restrain bale	Optional bolt-on side bars	Heavy-duty drive dog system

SL-350 SPECIFICATIONS

BALE SIZES ROUND: 4' X 4' - 6' X 5'
BALE SIZES SQUARE: requires optional side bars
BALE WEIGHT: up to 1000kg
UNIT WEIGHT: 460kg
HYDRAULICS REQUIRED: 1 X double-acting, 12-60 litres/min, 2250-3000 psi

OPTIONAL EXTRAS:

- Side bar kit to feed square bales up to 6' 6" long
- Hydraulic top link
- String box (available 2008)

SL-350 LOADING SEQUENCE

