

VMX Toolcarrier Farm

Tool mounting system

- Up to 1500kg lifting capacity
- Up to 3.0m lift height
- Hustler clearview design mast
- Optional hydraulic toplink
- Can be adapted to fit the front of the tractor
- Accepts Eurohitch implements
- Around half the cost of a front end loader

Handling Solution

A new handling situation has arisen for farmers as more and more bulk goods arrive to the farm on pallets.

VMX Toolcarrier Farm is an innovative and versatile new concept which gives farmers a convenient, cost effective alternative to a front-end loader. It is excellent as a secondary lifting unit on the farm.

VMX Toolcarrier can be quickly and easily fitted to any tractor on your farm via its 3 point linkage and has several important advantages when handling these types of goods.

VMX TOOLCARRIERS ADVANTAGES

- The weight is carried over the rear wheels giving increased stability, safety and manoeuvrability.
- The mast lifts straight up and down to a height of up to 3 metres, not in an arc like a front loader, again keeping the weight close to the rear wheels.
- Excellent stability over rough ground.
- Fitting a VMX Toolcarrier on a reserve tractor is a very cost effective option.

EUROHITCH CONVENIENCE

VMX Toolcarrier Farm incorporates the industry standard Eurohitch fitment, allowing any Eurohitch attachments to be fitted.

Bale grabs, bale forks, pallet forks, in fact almost anything you would normally attach to your 3 point linkage, can be fitted.* And with VMX Toolcarrier fitted you can still hitch a trailer to your drawbar.

*Eurohitch brackets will need to be welded to your 3 point linkage implements



Big bale handling



Lifting through the loops




1300kg pallet load

"The main reason we have a toolcarrier is to feed out to calves with a gravity feed tank on the forks. The other main reason is to handle pallets of calf meal, milk powder, cosmag and other animal health products. The delivery guys love it, as it is so quick to off-load and they can go."

DAIRY FARMER, TARANAKI: VMX TOOLCARRIER 2/12/2.7

VMX TOOLCARRIER FARM SPECIFICATIONS


- LIFTING CAPACITY: 1500kg
- LIFT HEIGHT: up to 3.0m
- UNIT WEIGHT: 240kg
- HYDRAULICS REQUIRED: 1 X single-acting 12-60 litres/min, 2250-3000 psi • double-acting for tilt • double-acting for 3rd service



MANOEUVRABLE


Approximately twice as manoeuvrable as a front-end loader

STABLE




More stable than front-end loader

VERTICAL LIFT



Lifts vertically not in arc, also self-levelling

LIFT CAPACITY



Lifts up to 1.5t (depending on tractor size)

QUICK ATTACH



Attach implements quickly with Eurohitch

FORKLIFT

