



GT SERIES TIP TRAILERS

NZ MADE TRAILERS

SINCE 1959

Re-imagine what you know about tip trailers.

We re-visited and re-engineered the tip trailer concept to launch the GT series with a tougher, smarter and more user-friendly design totally suited to NZ farming conditions. Offered in various capacities ranging from 6 tonnes to 18 tonnes, a larger deck size offers up to 15% more capacity than the previous models, and newly designed side boards slam shut and self-lock with clever heavy-duty latches.



KEY FEATURES	BENEFITS
Larger deck and higher sides	Carry more volume and easily lift the rated tonnage. We design all trailers to lift about 30% more than the stated load
Slam shut latches	Easy to open and close by yourself. The clever design locks tighter with trailer movement
Free-standing tailgate with solid rear supports	Quickly drop or remove the sides without having to take the tailgate off
A side-hinged tailgate kit can be retro-fitted	Easily add a side swinging tailgate for more flexibility
Auto-trip tailgate	A wire rope and spring release latch trips the gate automatically at a preset deck angle
The swivel towing eye is flange mounted	Simple to swap for a K80 ball hitch or easily replace for maintenance
Steep 54-degree tip angle	Easily tips off any type of load
Removable front board	Quick and easy to remove for carrying longer loads
Excellent ground clearance when tipped	Great for building stockpiles and means you won't get stuck or bulldoze the ground
Timber or steel deck	Choose what suits you - all for the same price
Heavy-duty rope rails	Securely tie down your loads

OPTIONAL EXTRAS

- Choose from a timber or steel deck
- Add a 2mm steel overlay deck as a toughened skin for a timber deck
- Add LED lights for great visibility and safety on the road
- Quick hitch stand to use with a Giltrap quick hitch for fast connection to the tractor
- Hydraulic tailgate release kit for more precise gate latch control
- 900mm hay extension extends the deck length for carrying bales
- K80 ball hitch connector instead of a swivel towing eye. Safe and secure with reduced wear
- Different tyres -various tread patterns, diameters and ground pressure properties to suit your farm
- Hydraulic brakes for the front and rear axles. Can be operated from the tractor brake pedal or a remote hydraulic circuit



DIMENSIONS AND CAPACITIES

MODEL	GT6	GT8	GT10	GT14	GT17	GT20
Deck (L x W) in metres	3.6 x 2.4	4.2 x 2.4	4.7 x 2.4	5.0 x 2.4	5.25 x 2.7	5.5 x 2.7
Volume (m³)	3.6	5.7	6.4	7.9	9.5	11.5
Lift capacity (t)	6	8	10	14	17	20
Tipping angle (degrees)	57	57	57	57	57	57
Ram type (telescopic)	4 stage	4 stage	5 stage	5 stage	4 stage	6 stage
Sideboard height (mm)	460	600	600	700 (2 piece)	700 (2 piece)	800 (2 piece)
Tare weight (kg)	1825	2590	3160	3600	TBC	TBC
Axle size (mm)	60 (6 stud)	70 (6 stud)	80 (8 stud)	80 (8 stud)	90 (8 stud)	100 (8 stud)
Wheels	11.5/80-15.3	400/60-15.5	400/55-22.5	500/45-22.5	500/60-22.5	560/60-22.5

NEW ZEALAND HEAD OFFICE
TEL +64 7 873 4199
EMAIL info@giltrapag.co.nz
giltrapag.co.nz